

# 4800L ACTIVE HIGH PROFILE SPRAY TANK

## PRODUCT SPECIFICATION SHEET



### UNIT SPECIFICATIONS

Item	Description	Details
Tank	4800L	UV stabilised chemical resistant polyethylene tank, Complies with AS2070:1999 & AS4766:2006, Integral fully draining sump, 25 year warranty. Made in Australia
Lid	450mm	450mm screw lid fitted with spring breather valve and gasket
Tank Outlet	2" Croc-Loc	Stainless steel bolted flanged tank fitting
Colour	Teal	<i>*Note that tank colour can be customised</i>
Load Rating		1.3 Specific Gravity (SG)
Ball Baffles	ARB355 (Optional)	120 x ARB355F, Made from food grade polypropylene
Mounting Pins	Galvanised steel mounting frame and straps	Hot dipped galvanised steel mounting frame for correct tank support and to give sump clearance for access

### TANK MODELS

Product Code	Model Variant / Type	Dimension	Dry Weight
PTSP04800TT	Tank only	2340mm (L) x 1550mm (W) x 2080mm (H)	200kg
PTSP04800KTT	Tank with frame fitted	2340mm (L) x 1550mm (W) x 2130mm (H)	300kg



DISCOVER  
SAFER  
TANKERS  
WITH BALL  
BAFFLES.  
SCAN NOW!

