PRODUCT SPECIFICATION SHEET

MARSHAL DISINFECTANT SPRAYER 250L COMPACT DISINFECTANT SPRAYER





Manual Marshal Disinfectant Sprayer PCU1884



Buddy Marshal Disinfectant Sprayer PCU1885

MARSHAL DISINFECTANT SPRAYERS

SPRAYER SPECIFICATIONS

Item	Description	Details		
Tank	250L	UV stabilised chemical resistant polyethylene tank with moulded tie-down points. 15 year guarantee. AS2070:1999 compliant		
Mounting	Frame	Galvanised plate with 5year warranty		
Pump	Maruyama	33L/min 580 psi max, Triplex piston pump with 3 year warranty		
Motor	Honda GX200	4 stroke, overhead valve, single cylinder. 4.1kW @ 3600rpm. 3 year warranty		
Regulator	Brass or Nylon	3 outlets, pressure gauge, easy adjustment		
Hose Reel	50m manual	UV stabilised poly hose reel on galvanised steel frame, full flow ball bearing swivel, brass components, reel lock, rotating handle		
	50m auto reel	Buddy Smart Reel - 12/24V auto rewind hose reel with My-pace multiple speed remote, overrun protection, low voltage cut-out		
Spray Hose	10mm agricultural hose	l hose High flexibility, kink resistant, burst pressure 150 bar (2200 psi), working pressure 40 bar (580psi)		
Spray Gun	Turbo 400	Adjustable turbo atomiser, swivel, Viton seals, alloy handle, 725psi, 400mm length, 2.3mm nozzle		
Filter	1¼" or 1½"	32 mesh screen filter, auto shut-off system for easy cleaning with full tank		
Lid	250mm (2)	Threaded lid assembley with fixed labyrinth breather valve, UV stabilised		
Drain	11/4"	High volume quick drain located at front (pump end) of tank		

Tank Capacity	Length	Width	Height	
250L	910mm	730mm	940mm	