## PRODUCT SPECIFICATION SHEET

## MARSHAL PRO

**250L UTV SPRAYER** 







Marshal Pro

Buddy® Marshal Pro

## MARSHALL PRO | BUDDY® MARSHAL PRO

## **SPRAYER SPECIFICATIONS**

Item	Description	Details	
Tank	250L	UV stabilised chemical resistant polyethylene tank with moulded tie-down points. 15 year guarantee. AS2070:1999 compliant	
Mounting	Frame	Galvanised plate with	
Pump	Maruyama	33L/min 580 psi max, Triplex piston pump with 3 year warranty	
Motor	Honda GX200	4 stroke, overhead valve, single cylinder. 4.1kW @ 3600rpm. 3 year warranty	
Regulator	Brass or Nylon	3 outlets, pressure gauge, easy adjustment	
Hose Reel	30/50m manual	UV stabilised poly hose reel on galvanised steel frame, full flow ball bearing swivel, brass components, reel lock, rotating handle	
	50/100m auto reel	Buddy Smart Reel - 12/24V auto rewind hose reel with My-pace multiple speed remote, overrun protection, low voltage cut-out	
Spray Hose	pray Hose 10mm agricultural hose High flexibility, kink resistant, burst pressure 150 bar (2200 psi), working pressure 40 bar (5		
	8mm agricultural hose	Black Nylon high flexibility, kink resistant, burst pressure 1000 psi	
Spray Gun	Pistol Grip	stol Grip With swivel and Teflon seals, 800psi, 15 - 25L/min max, 180mm length	
	Turbo 400	Adjustable turbo atomiser, swivel, Viton seals, alloy handle, 725psi, 400mm length	
Filter	1¼" or 1½"	32 mesh screen filter, auto shut-off system for easy cleaning with full tank	
Lid	250mm (2)	Threaded lid assembley with fixed labyrinth breather valve, UV stabilised	
Drain	11/4"	High volume quick drain located at front (pump end) of tank	

Tank Capacity	Length	Width	Height
250L	910mm	730mm	940mm