


1500L ACTIVE SQUAT SPRAY TANK

PRODUCT SPECIFICATION SHEET



UNIT SPECIFICATIONS

| Item | Description | Details |
|---------------|--|--|
| Tank | 1500L | UV stabilised chemical resistant polyethylene tank, Complies with AS2070:1999 & AS4766:2006, Integral fully draining sump, 25 year warranty. Made in Australia |
| Lid | 450mm | 450mm screw lid fitted with spring breather valve and gasket |
| Tank Outlet | 1 1/2" MBSP | Flanged polypropylene tank outlet fitting complete with nut and washer |
| Colour | Teal | <i>*Note that tank colour can be customised</i> |
| Load Rating | | 1.3 Specific Gravity (SG) |
| Ball Baffles | ARB355 (Optional) | 37 x ARB355F, Made from food grade polypropylene |
| Mounting Pins | Galvanised steel mounting frame and straps | Hot dipped galvanised steel mounting frame for correct tank support and to give sump clearance for access |

TANK MODELS

| Product Code | Model Variant / Type | Dimension | Dry Weight |
|---------------|------------------------|-------------------------------------|------------|
| PTSP01500ATT | Tank only | 1800mm (L) x 1320mm (W) x 920mm (H) | 76kg |
| PTSP01500AKTT | Tank with frame fitted | 1640mm (L) x 1320mm (W) x 970mm (H) | 91kg |



DISCOVER
SAFER
TANKERS
WITH BALL
BAFFLES.
SCAN NOW!

