

# 2500L ACTIVE LOW PROFILE SPRAY TANK

## PRODUCT SPECIFICATION SHEET



### UNIT SPECIFICATIONS

Item	Description	Details
Tank	2500L	UV stabilised chemical resistant polyethylene tank, Complies with AS2070:1999 & AS4766:2006, Integral fully draining sump, 25 year warranty. Made in Australia
Lid	450mm	450mm screw lid fitted with spring breather valve and gasket
Tank Outlet	2" MBSP	Flanged polypropylene tank outlet fitting complete with nut and washer
Colour	Teal	<i>*Note that tank colour can be customised</i>
Load Rating		1.3 Specific Gravity (SG)
Ball Baffles	ARB355 (Optional)	62 x ARB355F, Made from food grade polypropylene
Mounting Pins	Galvanised steel mounting frame and straps	Hot dipped galvanised steel mounting frame for correct tank support and to give sump clearance for access

### TANK MODELS

Product Code	Model Variant / Type	Dimension	Dry Weight
PTSP02500TT	Tank only	2000mm (L) x 1480mm (W) x 1310mm (H)	105kg
PTSP02500KTT	Tank with frame fitted	2000mm (L) x 1480mm (W) x 1360mm (H)	145kg



DISCOVER  
SAFER  
TANKERS  
WITH BALL  
BAFFLES.  
SCAN NOW!

