

# 400L ACTIVE LOW PROFILE SPRAY TANK

## PRODUCT SPECIFICATION SHEET



### UNIT SPECIFICATIONS

Item	Description	Details
Tank	400L	UV stabilised chemical resistant polyethylene tank, Complies with AS2070:1999 & AS4766:2006, Integral fully draining sump, 25 year warranty. Made in Australia
Lid	255mm	255mm screw lid fitted with spring breather valve and gasket
Tank Outlet	1 1/2" MBSP	Flanged polypropylene tank outlet fitting complete with nut and washer
Colour	Teal	<i>*Note that tank colour can be customised</i>
Load Rating		1.3 Specific Gravity (SG)
Ball Baffles	ARB195 (Optional)	57 x ARB195F, Made from food grade polypropylene
Mounting Pins	Galvanised steel mounting frame and straps	Hot dipped galvanised steel mounting frame for correct tank support and to give sump clearance for access

### TANK MODELS

Product Code	Model Variant / Type	Dimension	Dry Weight
PTSP00400ATT	Tank only	1140mm (L) x 1050mm (W) x 610mm (H)	26kg
PTSP00400AKTT	Tank with frame fitted	1140mm (L) x 1050mm (W) x 650mm (H)	43kg



DISCOVER  
SAFER  
TANKERS  
WITH BALL  
BAFFLES.  
SCAN NOW!

