

FIELDLINK PRO LINKAGE SPRAYER

400L / 600L / 800L

PRODUCT SPECIFICATION SHEET



800L FieldLink Pro

UNIT SPECIFICATIONS

Item	Description	Details
Tank	400L, 600L, 800L	Australian made rotationally moulded UV stabilised chemical resistant polyethylene tank with integral sump. Graduated sight tube installed. 25 year guarantee*. AS2070:1999 compliant
Lid	450mm / 250mm	450mm opening on main tank for easy access. 250mm on hand wash tank. "No-splash" breathers fitted
Mounting	Frame	Galvanised forklift pockets. Category 1, 2 and 3 pins
Pump	Bertolini Poly 2073	75L/min 215 psi max. Liquid fertiliser ready. Made in Italy. 3 year warranty.
Regulator	4-way Multi-controller	Modular Arag regulator with glycerine filled pressure gauge for clear pressure readings, rotating knob for easy pressure adjustment and pressure dump/bypass lever.
Flush Tank	40L (400L) 70L (600L / 800L)	Flush tank with 3 way changeover valve for complete rinsing of pump, regulator and boom with fresh water. Sight tube installed.
Hand Wash Tank	Built-in	Integrated 15L handwash tank with easy to access tap for safety
Hose	15m	Premium braided Australian made spray hose
Gun	AHG109	Powerjet spray gun with adjustable brass nozzle and accidental trigger lock
PTO Shaft	Adjustable	Supplied adjustable PTO shaft with guards
Booms	-	Ready to accept 4m / 6m / 8m booms
Custom Fit Options		See pricelist.

SPRAYER DIMENSIONS (mm)

TANK CAPACITY	LENGTH	WIDTH	HEIGHT
400L	940	750	1180
600L	1230	890	1550
800L	1200	890	1750

* 15 years full, 10 years pro rata