

ULTIMATE FIRE FIGHTER UNIT

400L / 600L / 800L / 1000L

PRODUCT SPECIFICATION SHEET



600L Ultimate Fire Fighter:
1950 L x 1360 W x 700 H

UNIT SPECIFICATIONS

Item	Description	Details
Tank	400L - 1000L	Tanks manufactured from specifically formulated diesel grade polyethylene meeting ECE R34.01 & AS 1940-2004, AS 2809.2-2008 requirements. 15 Year full replacement warranty.
Tank Mounting	Frame	Galvanised steel frame with mounting pins 18mm x 200mm
Pump	RapidPro Fire Pump	40 bar 580 psi, 450 L/min 5 Year warranty
Engine	Honda GX200	4 stroke overhead valve, single cylinder 4.1kw @ 3600rpm. 3 year warranty
Hose		36m x 19mm fire fighting hose
Reel	Poly manual	UV stabilised poly hose reel on galvanised steel frame, full flow ball bearing swivel, brass components, reel lock, rotating handle
Lid	255mm	Threaded lid assembly with fixed labyrinth breather valve. UV Stabilised (400L / 600L)
	455mm	180 hinged tank lid, fixing ring labyrinth breather valve, gasket seal, six point bayonet lock, UV stabilised (800L / 1000L)
Drain	Integral Sump	Positive draining tank base with integral sump with 1 1/4" MBSP poly tank fitting with gasket
Ball Baffles		Ball Baffle System for stability (optional upgrade)

ULTIMATE FIRE FIGHTER UNIT

400L / 600L / 800L / 1000L

PRODUCT SPECIFICATION SHEET



DIMENSIONS

SIZE	L (mm)	W (mm)	H (mm)
400L	1950	1360	700
600L	1950	1360	700
800L	1950	1360	890
1000L	1950	1360	1045



UPGRADE OPTIONS

BALL BAFFLES® – ARB195 / ARB355

- Small Ball Baffle Ø195mm - suits 600L
- Large Ball Baffle Ø355mm - suits 800L-1000L



BOTTOM FILL KIT – AFK006

- 6m hose
- Camlock fittings
- Foot strainer

